

THE CLAIMS

What is claimed is:

- 5 1. A tool holder for mounting to a user's clothing article, comprising:
a first support member of an injection-molded material;
a second support member connected to the first support member at a
connection portion, wherein the first and second support members are configured and
dimensioned for receiving and hooking around the article with the first and second support
10 members disposed on opposite sides of the article; and
a tool holding member mounted to one of the support members and
configured for receiving and holding a portion of a handheld tool.
- 15 2. The tool holder of claim 1, wherein the first and second support
members are of injection molded plastic.
3. The tool holder of claim 2, wherein the first and second support
members are pieces of separate construction that are joined to each other.
- 20 4. The tool holder of claim 2, wherein the first and second support
members are a single piece of unitary construction.
5. The tool holder of claim 1, wherein at least one of the support
members comprises a stiffening rib extending therefrom and configured for stiffening said
25 at least one support member.
6. The tool holder of claim 5, wherein the stiffening rib comprises a
plurality of stiffening ribs arranged substantially forming a truss.
- 30 7. The tool holder of claim 1, wherein the first support member has a
back surface facing away from the second support member and disposed for placement

against a user's waist, the back surface being curved to generally follow the curve of the user's waist.

8. The tool holder of claim 7, wherein:

the support members are connected to each other and define a article space therebetween configured to receive the article; and

the first support member has a curved surface facing the article space and disposed to contact the article received therein.

9. The tool holder of claim 1, wherein the first support member

comprises a first bottom end disposed below the connection portion and has a height between the connection portion and the first bottom end, the first support member comprises first and second legs extending along more than about half of the height of the first support member.

10. The tool holder of claim 1, wherein the tool holding member defines an opening to receive and hold the portion of the tool, the opening being of sufficient size to receive a cylindrical object having a diameter of at least about a ½ inch.

11. The tool holder of claim 1, wherein said one support member comprises a recessed mounting portion for attaching with a correspondingly shaped mounting portion of the tool holding member.

12. A tool holder for mounting to a user's clothing article, comprising:
a first support member;

a second support member connected to the first support member at a connection portion, wherein the first and second support members are configured and dimensioned for receiving and hooking around the article with the first and second support members disposed on opposite sides of the article; and

a tool holding member mounted to the second support member and having an operative position extending from the second support member for receiving and holding

a portion of a hand-held tool and being retractable to a retracted position for decreasing the bulk of the tool holder.

13. The tool holder of claim 12, wherein the tool holding member is
5 disposed substantially flush against the second support member in the retracted position.

14. The tool holder of claim 12, wherein the tool holding member is
pivotally connected to the second support member for pivoting between the operative and
retracted positions.
10

15. The tool holder of claim 14, wherein:
the second support member comprises a front face facing away from the
second support member; and
the tool holding member is pivotable towards and away from the front face.
15

16. A tool holder for mounting to a user's clothing article, comprising:
a first support member;
a second support member connected to the first support member at a
connection portion, wherein the first and second support members are configured and
20 dimensioned for receiving and hooking around the article with the first and second support
members disposed on opposite sides of the article;

a tool holding member mounted to the second support member and
configured for receiving and holding a portion of a hand-held tool; and
a secondary tool holding member associated with at least one of the support
25 members and tool holding member and configured for holding a second tool.

17. The tool holder of claim 16, wherein the secondary tool holding
member defines at least one secondary tool recess configured and dimensioned for receiving
and holding the secondary tool.
30

18. The tool holder of claim 17, wherein the recess has a ribbed,
substantially cylindrical portion configured and dimensioned for holding a drill tip.

19. The tool holder of claim 18, wherein:

at least one of the support members defines a grasping recess that is
sufficiently large to permit grasping by a user of a portion of a secondary tool disposed
5 therein;

the secondary tool holding member is disposed for access thereto by the user
in the grasping recess;

the grasping recess and secondary tool holding members being configured
for holding the secondary tool in the secondary tool holding member with a graspable
10 portion of the secondary tool protruding from the secondary tool holding member and
disposed graspably within the grasping recess.

20. The tool holder of claim 16, wherein the secondary tool holding
member comprises at least one resilient protrusion for engaging a recess of the secondary
15 tool.

21. The tool holder of claim 20, wherein the secondary tool holding
member comprises a plurality of resilient protrusions configured and dimensioned for
engaging a socket for a socket wrench.

20

22. The tool holder of claim 21, wherein the resilient protrusions are
movable with respect to each other to accommodate differently sized sockets.

23. A tool holder for mounting to a user's clothing article, comprising:
25 a first support member having a first bottom end and a first connection
portion disposed upwards from the first bottom end;

a second support member having a second bottom end and a second
connection portion disposed upwards from the second bottom end, wherein the first and
second connection portions are securable to each other in attached association, the first and
30 second support members being configured and dimensioned for receiving and hooking
around the article with the first and second support members disposed on opposite sides of
the article; and

a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool.

24. The tool holder of claim 23, wherein the connection portions are
5 configured for engagement with each other.

25. The tool holder of claim 24, further comprising a locking portion associated with the support members for locking the support members together in secured association.
10

26. The tool holder of claim 23, wherein:
at least one of the connecting portions comprises a connecting extension; and
at least the other of the connecting portions comprises a connecting recess
configured to engage the connecting extension for securing the first and second connecting
15 portions to each other.

27. The tool holder of claim 23, wherein the first and second support members are substantially coupled to each other with the connecting portions in the attached association.
20

28. The tool holder of claim 23, wherein the second support member and tool holder comprise a plurality of second support members and tool holders having different configurations for holding different tools.

29. A tool holder for mounting to a user's clothing article, comprising:
a first support member;
a second support member having a front face and connected to the first support member at a connection portion, wherein the first and second support members are configured and dimensioned for receiving and hooking around the article with the first and
25 second support members disposed on opposite sides of the article; and
a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool;
30

wherein the front face comprises a recess facing the tool holding member and configured and dimensioned for receiving another portion of the tool held in the tool holding member.

5 30. The tool holder of claim 29, wherein the tool holding member has a generally rounded portion defining a rounded shape for holding a round portion of the tool, and the recess comprises an indentation in the second support member disposed substantially concentrically with the rounded shape of the tool holding member.

10 31. A tool holder for mounting to a user's clothing article, comprising:
a first support member;
a second support member connected to the first support member at a connection portion, wherein the first and second support members are configured and dimensioned for receiving and hooking around the article with the first and second members
15 disposed on opposite sides of the article;
a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool, the tool holding member including a notch configured for receiving and positioning a portion of the tool in a predetermined orientation.

20 32. A tool holder for mounting to a user's clothing article, comprising:
a first support member;
a second support member connected to the first support member at a connection portion, wherein the first and second support members are configured and
25 dimensioned for receiving and hooking around the article with the first and second members disposed on opposite sides of the article; and
a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool;
wherein at least one of the first and second support members comprises a
30 projection facing the other of the support members for resisting removal of the tool holder from the article.

33. A tool holder for mounting to a user's clothing article, comprising:
a first support member;
a second support member connected to the first support member at a
connection portion, wherein the first and second support members are configured and
5 dimensioned for receiving and hooking around the article with the first and second members
disposed on opposite sides of the article;

a tool holding member mounted to the second support member and defining
a tool space configured for receiving and holding a hand-held tool, the tool holding member
defining first and second openings on opposite sides of and communicated with the tool
10 space, wherein the first opening is larger than the second opening for receiving a larger
portion of the tool than the second opening.

34. A tool holder for mounting to a user's clothing article, comprising:
first and second support members configured to cooperatively receive and
15 hook around the article with the first and second members disposed on opposite sides of the
article;

a tool holding member having a mounting portion and configured for
receiving and holding a portion of a hand-held tool, wherein the second support member
comprises a receiving recess, and the holding member mounting portion is received and
20 supported in the recess; and

a closure attached adjacent the recess for closing the recess and retaining the
holding member mounting portion pivotally therein.

35. A tool holder for mounting to a user's clothing article, comprising:
25 first and second support members configured to cooperatively receive and
hook around the article with the first and second members disposed on opposite sides of the
article;

a tool holding member having a mounting portion and configured for
receiving and holding a portion of a hand-held tool; and

30 a mount pivotally attached to the second support member and pivotally
supporting the holding member, wherein the mount has first and second portions disposed
about the holding member to trap the holding member in the mount.

36. A tool holder for mounting to a user's clothing article, comprising:
first and second support members configured to cooperatively receive and
hook around the article with the first and second members disposed on opposite sides of the
5 article;

a tool holding member having a mounting portion that is mounted to the
second support member is configured for receiving and holding a portion of a hand-held
tool; and

a deflecting ramp disposed adjacent to the mount and configured and angled
10 for deflecting impact from the tool as it is placed moved towards the tool holding member
to be held thereby.

37. A tool holder for mounting to a user's clothing article, comprising:
first and second support members configured to cooperatively receive and
15 hook around the article with the first and second members disposed on opposite sides of the
article;

a tool holding member having a mounting portion that is mounted to the
second support member is configured for receiving and holding a portion of a hand-held
tool; and

20 a retaining member configured for attaching the tool holding member to the
second support member, the retaining member being in a snap-fit association with the
second support member.